



107R2

Hydraulic puller 25 kN capacity for single rope pulling on overhead stringing operations as well as underground cabling.



Performance

Max pull	25 kN
Max speed	5 km/h
Speed at max pull	1 km/h

Characteristics

Bull-wheels diameter	250 mm
Max rope diameter	10 mm
Weight	950 kg

Engine

Diesel	(25 hp) 18,6 kW
Cooling	Liquid
Emission standard - [UE]2016/1628	Stage V

Standard features

- 1 hydraulic circuit with negative brake system
- 1 dynamometer for direct reading of pulling value with load-limiter device
- Thermally treated steel bull-wheels
- Automatic reel-winder suitable for steel reel 1100-1400 mm
- Rigid axle with tyres for towing up to 30 km/h
- Balanced top lifting point and anchoring attachments

Optional equipment

- 01-PW Preset for digital data recorder, counter-meter and speedometer
- 06-PW Front pulley roller guided device for underground cabling (Telescopic rod cod. AT1.30 on request)
- 07-PW Hydraulic power take-off for remote reel-winder

Special features upon request

- 03-PW Remote control unit c/w console 5 m cable
- 04-PW Radio control unit
- 05-PW Rope holder clamp (hydraulic)
- 13-PW Pre-heater (up to -30°C)
- 18-PW Counter-meter device
- 20-PW Dynamic speed pulling force control

