107R10

Hydraulic puller 100 kN capacity for single rope pulling on overhead stringing operations.



| Performance | |
|-----------------------------------|-----------------|
| Max pull | 100 kN |
| Max speed | 5 km/h |
| Speed at max pull | 2,1 km/h |
| Characteristics | |
| Bull-wheels diameter | 550 mm |
| Max rope diameter | 22 mm |
| Weight | 4250 kg |
| Engine | |
| Diesel | (143 hp) 105 kW |
| Cooling | Liquid |
| Emission standard - (UE)2016/1628 | Stage V |

Standard features

- 1 hydraulic circuit with negative brake system
- 1 dynamometer for direct reading of pulling value with load-limiter device
- Thermally treated steel bull-wheels
- Automatic reel-winder suitable for steel reel 1100÷1400 mm
- Remote control unit c/w console 5 m cable
- · Rigid axle with tyres for towing up to 30 km/h
- · Balanced top lifting point and anchoring attachments

Optional equipment

- 01-PW Preset for digital data recorder, counter-meter and speedometer
- 04-PW Remote control unit
- 05-PW Rope holder clamp (hydraulic)
- 07-PW Hydraulic power take-off for remote reel-winder

Special features upon request

- 13-PW Pre-heater (up to -30°C)
- 18-PW Counter-meter device
- 20-PW Dynamic speed pulling force control

