



## AF1518.14

Hydraulic puller-tensioner 180 kN capacity stringing of up to 4 bundled conductors.



### Standard features

- 1 hydraulic circuit with negative brake system
- 1 dynamometer for direct reading of pulling value with load-limiter device (puller-mode)
- 1 counter-meter device
- 4 sets of quick release hydraulic connectors to feed up to 4 remote reel-stands or 1 reel-winder unit
- Thermally treated steel adherence wheels
- Remote control unit c/w console 5 m cable
- Rear independent hydraulic stabilizers
- Rigid axle with tyres for towing up to 30 km/h
- Balanced top lifting point and anchoring attachments

### Optional equipment

- 01-PT Preset for digital data recorder, counter-meter and speedometer
- 04-PT Radio control unit
- 07-PT Hydraulic power take-off for press
- 08-PT Conductor/rope holder clamp (hydraulic)
- 15-PT Adherence wheels with interchangeable nylon liners
- 18-PT Multiple connection preset

### Special features upon request

- 02-PT Dynamic speed pulling force control
- 05-PT Additional hydraulic power take-off for reel-winder unit
- 20-PT Pre-heater (up to -30°C)
- 42-PT Engine emission standard Stage IIIA - (300 hp) 224 kW

### Puller performance

Max pull	180 kN
Max speed	5 km/h
Speed at max pull	2,1 km/h

### Tensioner performance

Max tension	180 kN
Max speed	5 km/h

### Characteristics

Adherence-wheels diameter	1500 mm
Also available with diameter	1800 mm
Max conductor diameter	42 mm
Max rope diameter	28 mm
Weight	12000 kg

### Engine

Diesel	(286 hp) 210 kW
Cooling	Liquid
Emission standard - (UE)2016/1628	Stage V

