EQUIPMENT FOR OVERHEAD CONDUCTORS STRINGING

400/04 - 400/05 - 400/07


CONDUCTOR SELF-GRIPPING CLAMPS

Suitable for A.C - AAC - ACSR and copper conductors.

Made of hot forged, heat treated, and cadmium plated high tensile alloy steel.

A complete range of interchangeable aluminum liners allows the clamp to fit the exact conductor diameter.

Each model of clamp is suitable for a wide range of conductors, therefore, the same clamp can be used for different conductors only by replacing aluminum liners.



MODEL	Conductor Ø	Working load	S.W.L	Breaking load	Weight
	mm	daN	daN	daN	kg
400-04	30 ÷ 45	5500	9170	28500	17,0
400-05	10 ÷ 33,5	4700	7830	23500	13,5
400-07	6 ÷ 23	3000	5000	15000	7,0

NOTE: Upon placing the purchase order, please specify conductor overall diameter or liners' measure.



410/04 — 410/05 — 410/07

LINERS FOR CONDUCTOR CLAMPS

LINERS FOR 400/04				
Conductor Ø	Liners code for	Liners for round	Liners for square pilot	
mm	aluminum conductor	shape steel rope	steel rope	
30-31,5	410-04-13			
31,5-33,0	410-04-14			
33-34,5	410-04-15	'	For range	
34,5-36	410-04-16		16-28mm,	
36-37,5	410-04-17		the liners	
37,5-39	410-04-18		are produced according to the	
39-40,5	410-04-19	the exact rope	exact rope	
From 40,5 to 45		diameter	diameter	
specify				
conductor Ø				



LINERS FOR 400/05				
Conductor Ø	Liners code for	Liners for round	Liners for square pilot	
mm	aluminum conductor	shape steel rope	steel rope	
10-12	410-05-00			
12-13,5	410-05-01			
13,5-15	410-05-02			
15-16,5	410-05-03			
16,5-18	410-05-04	For range	For range	
18-19,5	410-05-05	13-22mm.	13-24mm.	
19,5-21	410-05-06	the liners	the liners	
21-22,5	410-05-07	are produced	are produced	
22,5-24	410-05-08	according to	according	
24-25,5	410-05-09	the exact rope	to the exact rope	
25,5-27	410-05-10	diameter	diameter	
27-28,5	410-05-11			
28,5-30	410-05-12			
30-32	410-05-13			
32-33,5	410-05-16			



LINERS FOR 400/07				
Conductor Ø	Liners code for	Liners for round shape	Liners for square pilot	
mm	aluminum conductor	steel rop	steel rope	
6-6,5	410-07-01			
6,5-8	410-07-02			
8-9,5	410-07-03			
9,5-11	410-07-04	For range	For range	
11-12,5	410-07-05	8-13mm, the liners	8-13mm, the liners	
12,5-14	410-07-06			
14-15,5	410-07-07	are produced according	are produced according	
15,5-17	410-07-08	to the exact	to the exact rope	
17-18,5	410-07-09	rope diameter	diameter	
18,5-20	410-07-10			
20-21,5	410-07-11			
21,5-23	410-07-12			



EQUIPMENT FOR OVERHEAD CONDUCTORS STRINGING

400/12


OPTICAL GROUND WIRE "OPGW" SELF-GRIPPING CLAMPS

Self-gripping clamps with interchangeable liners suitable for OPGW cables from 6 to 23 mm diameter.

Made of hot forged, heat treated, and cadmium plated high tensile alloy steel.

- Maximum working load 3000 daN
- Maximum safety load 5000 daN
- Breaking load 15000 daN
- Weight: 7 kg





410/12

OPTICAL GROUND WIRE "OPGW" CABLE LINERS

OPGW liners have been specifically designed to protect the optical fiber from any damage.

One set of liners consists of a lower liner made of polyurethane and an upper liner made of aluminum alloy. Liners are supplied in any size between diameters 6 and 23 mm.







400/09


WIRE ROPE AND COPPER CONDUCTORS SELF-GRIPPING CLAMPS

Self-gripping clamps suitable for wire rope and copper conductor with diameters ranging from 3 to 15 mm.

Made of hot forged, heat treated, and cadmium plated high tensile alloy steel.

- Maximum working load 980 daN
- Maximum safety load 1930 daN
- Breaking load 4900 daN
- Weight: 1,5 kg





400/11


SELF-GRIPPING CLAMPS

Self-gripping clamps with interchangeable liners suitable for aluminum, aluminum-steel, copper conductors and steel wires ranging from 7 to 16 mm diameter.

Made of hot forged, heat treated, and cadmium plated high tensile alloy steel.

- Maximum working load 1280 daN
- Maximum safety load 2135 daN
- Breaking load 6400 daN
- Weight 2,5 kg





LINERS FOR 400/11				
Conductor Ø	Liners for aluminum Liners for copper conducto		Liners for steel rope (round or	
mm	conductor	Linera for copper conductor	square shape rope)	
7-8,5	410-11-01	410-11-R01		
8,5-10	410-11-02	410-11-R02		
10-11,5	410-11-03	410-11-R03	Produced in range 7-13mm specifying	
11,5-13	410-11-04	410-11-R04	the exact rope Ø	
13-14,5	410-11-05	410-11-R05		
14,5-16	410-11-06	410-11-R06		

EQUIPMENT FOR OVERHEAD CONDUCTORS STRINGING


400/06

WIRE ROPE AND STEEL GROUND WIRE SELF-GRIPPING CLAMPS

Self-gripping clamps suitable for ground wires and wire ropes with diameters ranging from 7,5 to 18 mm. Made of hot forged, heat treated, and cadmium plated high tensile alloy steel.

- Maximum working load 2500 daN
- Maximum safety load 4170 daN
- Breaking load 12500 daN
- Weight: 7 kg






402

BOLTED CLAMPS

Made of galvanized steel, supplied with aluminum liners to suit A.C - AAC - ACSR and AAAC conductors or bronze liners to suit steel wire ropes.

NOTE: Upon placing the purchase order, please specify conductor overall diameter.



MODEL	N° of elements	Dimensions	Rope Ø	Conductor Ø	Working load
MODEL N of eleme	N OF ELEMENTS	A x B x L mm	mm	mm	kN
40204	4	150 x 150 x 390	20	15÷26	24
40206	6	150 x 150 x 510	24	20÷35	36
40207	7	150 x 150 x 580	28	20÷35	40
40208	8	150 x 150 x 650	30	30÷40	48
40210	10	150 x 150 x 800	30	30÷40	60
40212	12	150 x 150 x 922	36	30÷40	76
40214	14	150 x 150 x 1100	40	30÷40	90
40216	16	150 x 150 x 1166	45	35÷50	100
40220	20	150 x 150 x 1400	50	40÷60	120




400/08

SELF-GRIPPING CLAMPS FOR CONDUCTOR LIFTING

Self-gripping clamps with interchangeable liners suitable for lifting conductors with an overall diameter ranging from 7 to 38 mm.

Made of hot forged, heat treated, and cadmium plated high tensile alloy steel.

- Maximum working load 1960 daN
- Maximum safety load 3270 daN
- Breaking load 9800 daN
- Weight: 5,5 kg







LINERS FOR 400/08			
Conductor Ø	Liners for aluminum conductor		
mm	Liners for adminimum conductor		
7-11	410-08-01		
9-12	410-08-02		
12-16	410-08-03		
16-23	410-08-04		
22-36	410-08-05		
30-38	410-08-06		

Special liners available upon request

How to use





462

SADDLE TYPE CONDUCTOR LIFTING DEVICE

Lifting device for conductors.
Suitable for single as well as bundled conductors.
Available on request: coated version for conductor protection.

