




TC/...

RATCHET TYPE TURNBUCKLE

MODEL	Dimensions (mm)					Working load kg	Breaking load kg	Weight kg
	A min	A max	B	C	D			
TC 30	600	900	18	20	50	3000	9000	10
TC 50	650	1050	22	20	54	6000	18000	14
TC 100	950	1550	24	24	60	10000	30000	18



BF-RBT


TEMPORARY-ANCHORING CAPSTAN DEVICE

Suitable for rope anchoring. Complete with rope clamp to suit 10 to 20 mm diameter ropes. Aluminum alloy frame.

Working load: 500 daN

Breaking load: 1500 daN

Weight: 3,3 kg




209...

SHACKLES

High carbon steel shackles with high alloy steel pin.

MODEL	Capacity daN	Dimensions (mm)						Weight kg
		A	B	C	D	E	H	
209 0050	500	12	20	6	8	18	32	0,05
209 0075	750	13	21	8	10	21	36	0,08
209 0100	1000	16	26	10	11	25	42	0,1
209 0150	1500	18	29	11	13	27	49	0,2
209 0200	2000	20	33	13	16	31	55	0,3
209 0325	3250	27	43	16	19	40	70	0,7
209 0475	4750	32	51	19	22	48	82	1
209 0650	6500	37	58	22	25	55	97	1,5
209 0850	8500	43	68	26	28	61	109	2,4
209 0950	9500	46	74	29	32	67	124	3,2



309 AA

NOTE: Other sizes available on request

GALVANIZED STEEL SLINGS

With crimped eye both ends

Available on request:

- Sling supplied with metal core;
- Sling with thimble at each ends;
- Sling with rubber protection.



MODEL	Ø rope mm	Capacity (kg) (accordingly to the method of use)				Eye mm
309AA08...	8	700	1400	1210	990	64x128
309AA10...	10	1100	2140	1850	1510	80x160
309AA12...	12	1600	3200	2770	2260	96x192
309AA14...	14	2100	4160	3600	2940	112x224
309AA16...	16	2750	5460	4720	3860	128x256
309AA18...	18	3500	7000	6050	4950	144x288
309AA20...	20	4300	8560	7400	6050	160x320
309AA22...	22	5200	10300	8910	7280	176x352
309AA24...	24	6200	12400	10640	8690	192x384