


# ACCESSORI PER TESATURA AEREA CONDUTTORI

## CT...

### CALZA TIRACAVI DI TESTA



| MODELLO | Conduttore Ø | Dimensioni (mm) |      | Carico di lavoro | Peso |
|---------|--------------|-----------------|------|------------------|------|
|         | mm           | A               | B    | kN               | kg   |
| CT 0    | 7-11         | 900             | 1500 | 7                | 0,45 |
| CT 1    | 11-14        | 1000            | 1600 | 8                | 0,6  |
| CT 2    | 14-17        | 1050            | 1700 | 10               | 0,6  |
| CT 3    | 17-23        | 1150            | 1800 | 17               | 0,8  |
| CT 4    | 23-29        | 1300            | 2200 | 27               | 1,7  |
| CT 5    | 29-38        | 1550            | 2400 | 40               | 3    |
| CT 6    | 38-50        | 1650            | 2800 | 60               | 4,5  |

## CT...


### CALZA TIRACAVI DI GIUNZIONE



| MODELLO | Conduttore Ø | Dimensioni (mm) |      | Carico di lavoro | Peso |
|---------|--------------|-----------------|------|------------------|------|
|         | mm           | A               | B    | kN               | kg   |
| CT 00   | 7-11         | 900             | 2300 | 7                | 0,7  |
| CT 7    | 11-14        | 1000            | 2600 | 8                | 0,8  |
| CT 8    | 14-17        | 1050            | 2800 | 10               | 0,8  |
| CT 9    | 17-23        | 1150            | 3000 | 17               | 1,2  |
| CT 10   | 23-29        | 1300            | 3500 | 27               | 3,3  |
| CT 11   | 29-38        | 1550            | 4100 | 40               | 5    |
| CT 12   | 38-50        | 1650            | 4300 | 60               | 8,7  |

## CTT...

### CALZA TIRACAVI DI TESTA




| MODELLO  | Conduttore Ø | Dimensioni (mm) |      | Carico di lavoro | Peso |
|----------|--------------|-----------------|------|------------------|------|
|          | mm           | A               | B    | kN               | kg   |
| CTT 00   | 8-17         | 1100            | 1400 | 12               | 0,70 |
| CTT 00 R |              |                 |      | 17               | 0,90 |
| CTT 01   | 17-29        | 1360            | 1700 | 28               | 1,30 |
| CTT 01 R |              |                 |      | 33               | 1,50 |
| CTT 02   | 29-38        | 1470            | 1900 | 43               | 2,10 |
| CTT 02 R |              |                 |      | 50               | 2,50 |
| CTT 03   | 38-50        | 1820            | 2270 | 60               | 2,70 |
| CTT 03 R |              |                 |      | 70               | 3,00 |

NOTA: R = versione rinforzata

## CTG...

### CALZA TIRACAVI DI GIUNZIONE



| MODELLO  | Conduttore Ø | Dimensioni (mm) |      | Carico di lavoro | Peso |
|----------|--------------|-----------------|------|------------------|------|
|          | mm           | A               | B    | kN               | kg   |
| CTG 00   | 8-17         | 1100            | 2680 | 12               | 1,15 |
| CTG 00 R |              |                 |      | 17               | 1,25 |
| CTG 01   | 17-29        | 1360            | 3240 | 28               | 2,30 |
| CTG 01 R |              |                 |      | 33               | 2,50 |
| CTG 02   | 29-38        | 1470            | 3540 | 43               | 3,60 |
| CTG 02 R |              |                 |      | 50               | 3,80 |
| CTG 03   | 38-50        | 1820            | 4240 | 60               | 4,80 |
| CTG 03 R |              |                 |      | 70               | 5,00 |

NOTA: R = versione rinforzata